## **Listing of Claims:**

The following complete set of claims has been listed below. No amendments have been submitted in this response.

1. (Previously Amended) A device for manipulating a molecule *in vivo* relative to a target tissue comprising:

an elongated member comprising a generally cylindrical conductive core electrode;

a first nonconductive insulator sleeve positioned in surrounding relation to a portion of the core electrode, with a lower portion of the core electrode extending axially beyond the first insulator sleeve;

a first electrode member positioned in surrounding relation to a portion of the first nonconductive insulator sleeve, with a lower portion of the first insulator sleeve extending axially beyond the first electrode member;

a second nonconductive insulator sleeve positioned in surrounding relation to a portion of the first electrode member, with a lower portion of the first electrode member extending axially beyond the second insulator sleeve;

a second electrode member positioned in surrounding relation to a portion of the second insulator sleeve, with a lower portion of the second insulator sleeve extending axially beyond the second electrode member;

a third nonconductive insulator sleeve positioned in surrounding relation to a portion of the second electrode member, with a lower portion of the second electrode member extending axially beyond the third insulator sleeve, and wherein each electrode being in independent circuit communication with a respective portion of a source of electrical energy, the electrodes being configured to establish a first electromagnetic field *in vivo* between selected electrodes sufficient to cause an electromigration of a molecule relative to a target tissue and a second electromagnetic field sufficient to cause transient permeability of a cell membrane within the target tissue.

- 2. (Previously Amended) The device recited in Claim 1, wherein the second field is higher in strength than the first field.
- 3. (Original) The device recited in Claim 1, wherein the elongated member is geometrically adapted for insertion into the target tissue.
- 4. (Previously Amended) The device recited in Claim 1, wherein the core electrode has a tip positioned at a distal end of the core electrode.
- 5. (Original) The device recited in Claim 1, wherein the member comprises a plurality of members configurable to surround a periphery of at least a portion of the target tissue.
- 6. (Original) The device recited in Claim 1, wherein the member comprises a pair of members configured in spaced-apart relation and adapted to provide at least one pair of opposite-polarity voltages approximately simultaneously on at least one electrode on each member.
- 7. (Original) The device recited in Claim 1, further comprising means for selectively activating a selected plurality of electrodes in a predetermined pattern.
- 8. (Original) The device recited in Claim 1, wherein the electrodes are substantially simultaneously activatable.
- 9. (Original) The device recited in Claim 1, wherein the member has a lumen therethrough extending from an opening adjacent a top of the member to a portal positioned along the member beneath the top opening for passing a substance therethrough to the target tissue.
- 10. (Previously Amended) The device recited in Claim 9, wherein the portal is positioned adjacent a bottom tip of the member.
- 11. (Previously Amended) The device recited in Claim 9, wherein the portal is positioned along the member adjacent an electrode.
- 12. (Previously Amended) A device for manipulating a molecule *in vivo* relative to a target tissue comprising:

an elongated member comprising a generally cylindrical conductive core electrode;

a first nonconductive insulator sleeve positioned in surrounding relation to a portion of the core electrode, with a lower portion of the core electrode extending axially beyond the first insulator sleeve;

a first electrode member positioned in surrounding relation to a portion of the first nonconductive insulator sleeve, with a lower portion of the first insulator sleeve extending axially beyond the first electrode member;

a second nonconductive insulator sleeve positioned in surrounding relation to a portion of the first electrode member, with a lower portion of the first electrode member extending axially beyond the second insulator sleeve;

a second electrode member positioned in surrounding relation to a portion of the second insulator sleeve, with a lower portion of the second insulator sleeve extending axially beyond the second electrode member;

a third nonconductive insulator sleeve positioned in surrounding relation to a portion of the second electrode member, with a lower portion of the second electrode member extending axially beyond the third insulator sleeve, and wherein each electrode being in independent circuit communication with a respective portion of a source of electrical energy, the electrodes being configured to establish a first electromagnetic field *in vivo* between selected electrodes sufficient to cause at least one of an electromigration of a molecule relative to a target tissue and transient permeability of a cell membrane within the target tissue.

- 13. (Previously Added) The device of claim 1, further comprising a plurality of insulating sleeves and a plurality of electrode members.
- 14. (Previously Added) The device of claim 12, further comprising a plurality of insulating sleeves and a plurality of electrode members.